

	SAFETY DATA SHEET	Page : 1 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Derbiprimer GC
UFI : K110-60TQ-G009-SRW8
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial uses
Use of the substance/mixture : Further information: see technical data sheet. TDS Derbiprimer GC

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Imperbel N.V./S.A
Guido Gezellestraat 123
1654 Beersel (Huizingen), Belgium
Tel.+32 2 334 87 00
Fax:+32 2 378 14 69
info@derbigum.com
www.derbigum.be

1.4. Emergency telephone number

Emergency number : + 32 3 575 55 55 (24h/24h)

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)


SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]



Flam. Liq. 3 H226
STOT SE 3 H336
Aquatic Chronic 3 H412

Full text of H- and EUH-statements: see section 16

	SAFETY DATA SHEET	Page : 2 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)	:	 
		<small>GHS02 GHS07</small>
Signal word	:	Warning
Contains	:	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2%
Hazard statements (CLP)	:	H226 - Flammable liquid and vapour. H336 - May cause drowsiness or dizziness. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	:	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P261 - Avoid breathing fume, spray, mist, vapours. P273 - Avoid release to the environment. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents and container to an approved waste disposal plant.
Extra phrases	:	EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Other hazards : Vapours can form explosive mixtures with air.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2%	(CAS-No.) - (EC-No.) 927-241-2 (EC Index) - (REACH-no) 01-2119471843-32-xxxx	45 – 50	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

	SAFETY DATA SHEET	Page : 3 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)	(CAS-No.) 34140-91-5 (EC-No.) 251-846-4 (REACH-no) 01-2119974119-29-xxxx	0,5 – 2,5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 2, H411
---	--	-----------	---

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice	: First aider: Pay attention to self-protection!. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance.
Inhalation	: Remove casualty to fresh air and keep warm and at rest. In case of doubt or persistent symptoms, consult always a physician.
Skin contact	: Remove contaminated clothing and shoes. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.
Eyes contact	: Rinse immediately carefully and thoroughly with eye-bath or water. In case of doubt or persistent symptoms, consult always a physician.
Ingestion	: Rinse mouth thoroughly with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: May cause drowsiness or dizziness. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Skin contact	: Repeated exposure may cause skin dryness or cracking.
Eyes contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: carbon dioxide (CO ₂), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards	: Flammable liquid and vapour. Heating will cause a rise in pressure with a risk of bursting.
Explosion hazard	: Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Vapours may form explosive mixture with air.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Firefighting instructions	: Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.
---------------------------	---

	SAFETY DATA SHEET	Page : 4 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
- Other information : Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- For non-emergency personnel : Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately earthed. Use explosion-proof equipment. Use only non-sparking tools.

6.1.2. For emergency responders

- For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

- Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Dam up the solid spill.
- Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation. Cover the spilled liquid product with foam to slow down evaporation.


6.4. Reference to other sections

- Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8 . Avoid contact with skin, eyes and clothing. Do not breathe vapour/aerosol. Ensure equipment is adequately earthed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not smoke. After use replace the closing cap immediately. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Do not allow to enter into surface water or drains. Take any precaution to avoid mixing with combustibles...
- Hygiene measures : Use only in area provided with appropriate exhaust ventilation. Wash hands and face before breaks and immediately after handling of the product. When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs. Keep good industrial hygiene.

	SAFETY DATA SHEET	Page : 5 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage.
Incompatible substances or mixtures	: Strong oxidizing agents.
Heat and ignition sources	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Packaging materials	: Do not pierce or burn, even after use. Do not burn, or use a cutting torch on the empty drum. Never use pressure to empty container. Keep only in the original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters


8.2. Exposure controls

Engineering measure(s)	: Provide adequate ventilation. Use only in area provided with appropriate exhaust ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Take precautionary measures against static discharges. Organisational measures to prevent /limit releases, dispersion and exposure : Reference to other sections 7.
Personal protective equipment	: Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hand protection	: Protective gloves complying with EN 374. Recommended material: Nitrile rubber. Viton [®] . Barrier [®] (PE/PA/PE). The selection of specific gloves for a specific application and time of use in a working area, should also take into account other factors on the working space, such as (but not limited to): other chemicals that are possibly used, physical requirements (protection against cutting/drilling, skill, thermal protection), and the instructions/specification of the supplier of gloves.
Eye protection	: During splash contact: Safety glasses with side-shields (EN166).
Body protection	: Wear suitable protective clothing, gloves and eye/face protection.
Respiratory protection	: Usually no personal respirative protection necessary. In case of insufficient ventilation, wear suitable respiratory equipment. full face mask (DIN EN 136). Half-face mask (DIN EN 140). Filter type: A (EN141).
Environmental exposure controls	: Avoid release to the environment. Comply with applicable Community environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: viscous liquid.
Colour	: Black.
Odour	: Characteristic.
Odour threshold	: Not available
pH	: Not available

	SAFETY DATA SHEET	Page : 6 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

Relative evaporation rate (butylacetate=1)	: No data available
Melting / freezing point	: No data available
Freezing point	: No data available
Initial boiling point and boiling range	: 140 °C Initial boiling point
Flash point	: 35 °C (PMCC)
Auto-ignition temperature	: > 300 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 6 hPa (20°C)
Vapour density	: No data available
Relative density	: No data available
Density	: 0,89 g/ml
Solubility	: Water: Insoluble
Partition coefficient n-octanol/water	: No data available
Kinematic viscosity	: 25 mm ² /s (40°C)
Dynamic viscosity	: No data available
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Explosive limits	: No data available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

	SAFETY DATA SHEET	Page : 7 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

10.3. Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Handling and storage . Reference to other sections 7:

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

When heated to decomposition, emits dangerous fumes . Hazardous decomposition products due to incomplete combustion. Carbon monoxide .

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% (-)	
LD50/oral/rat	> 5000 mg/kg
LD50/dermal/rabbit	> 5000 mg/kg
Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1) (34140-91-5)	
LD50/dermal/rat	> 2000 mg/kg

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness. EC 927-241-2 : May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)


Derbiprimer GC	
Kinematic viscosity	25 mm ² /s (40°C)

Other information : Symptoms related to the physical, chemical and toxicological characteristics. Reference to other sections 4.2.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

	SAFETY DATA SHEET	Page : 8 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

11.2.2 Other information

Other information : Symptoms related to the physical, chemical and toxicological characteristics, Reference to other sections 4.2

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% (-)	
LC50 - Fish [1]	10 – 100 mg/l
NOEC (acute)	0,1 – 1 mg/l fish
Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1) (34140-91-5)	
LC50 - Fish [1]	1,35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

12.2. Persistence and degradability

Derbiprimer GC	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

Derbiprimer GC	
Ecology - soil	No information available.

12.5. Results of PBT and vPvB assessment


Derbiprimer GC	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Additional information : No information available

	SAFETY DATA SHEET	Page : 9 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

SECTION 13: Disposal considerations

13.1. Waste treatment methods






Product/Packaging disposal recommendations : Handle with care. Reference to other sections 7: Handling and storage . Do not allow to enter into surface water or drains. Dispose of contaminated materials in accordance with current regulations. Refer to manufacturer/supplier for information on recovery/recycling. Collect and dispose of waste product at an authorised disposal facility.

Additional information : Delivery to an approved waste disposal company.

European waste catalogue : Classified as hazardous waste according to European Union regulations. The following Waste Codes are only suggestions:
 waste paint and varnish containing organic solvents or other dangerous substances
 wastes from paint or varnish removal containing organic solvents or other dangerous substances
 Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities

SECTION 14: Transport information


In accordance with ADR / RID / IMDG / IATA / ADN


ADR	IMDG	IATA	ADN	RID
14.1. UN number				
3295	3295	3295	3295	3295
14.2. UN proper shipping name				
HYDROCARBONS, LIQUID, N.O.S.	HYDROCARBONS, LIQUID, N.O.S.	Hydrocarbons, liquid, n.o.s.	HYDROCARBONS, LIQUID, N.O.S.	HYDROCARBONS, LIQUID, N.O.S.
Transport document description				
UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, III, (D/E)	UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, III	UN 3295 Hydrocarbons, liquid, n.o.s., 3, III	UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, III	UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1
 Limited quantities (ADR) : 5I

	SAFETY DATA SHEET	Page : 10 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019


Excepted quantities (ADR) : E1
 Packing instructions (ADR) : P001, IBC03, LP01, R001
 Mixed packing provisions (ADR) : MP19
 Portable tank and bulk container instructions (ADR) : T4
 Portable tank and bulk container special provisions (ADR) : TP1, TP29
 Tank code (ADR) : LGBF
 Vehicle for tank carriage : FL
 Transport category (ADR) : 3
 Special provisions for carriage - Packages (ADR) : V12
 Special provisions for carriage - Operation (ADR) : S2
 Hazard identification number (Kemler No.) : 30
 Orange plates : 
 Tunnel restriction code : D/E
 EAC code : 3YE

- Transport by sea

Special provisions (IMDG) : 223
 Limited quantities (IMDG) : 5 L
 Excepted quantities (IMDG) : E1
 Packing instructions (IMDG) : P001, LP01
 IBC packing instructions (IMDG) : IBC03
 Tank instructions (IMDG) : T4
 Tank special provisions (IMDG) : TP1, TP29
 EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-D
 Stowage category (IMDG) : A
 Properties and observations (IMDG) : Immiscible with water.

- Air transport

PCA Excepted quantities (IATA) : E1
 PCA Limited quantities (IATA) : Y344
 PCA limited quantity max net quantity (IATA) : 10L
 PCA packing instructions (IATA) : 355
 PCA max net quantity (IATA) : 60L
 CAO packing instructions (IATA) : 366
 CAO max net quantity (IATA) : 220L
 Special provisions (IATA) : A3, A224
 ERG code (IATA) : 3L

	SAFETY DATA SHEET	Page : 11 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

- Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

- Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Derbiprimer GC ; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2%
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Derbiprimer GC ; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2%
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Derbiprimer GC ; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2%
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	Derbiprimer GC ; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2%

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances


	SAFETY DATA SHEET	Page : 12 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

15.1.2. National regulations

Danish product registration number 2321503

France

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4330.text	Liquides inflammables de catégorie 1, liquides inflammables maintenus à une température supérieure à leur point d'ébullition, autres liquides de point éclair inférieur ou égal à 60° C maintenus à une température supérieure à leur température d'ébullition ou dans des conditions particulières de traitement, telles qu'une pression ou une température élevée (1).		
4330.1	La quantité totale susceptible d'être présente dans les installations y compris dans les cavités souterraines étant : 1. Supérieure ou égale à 10 t (1) Conformément à la section 2.6.4.5 de l'annexe I du règlement (CE) n° 1272/2008, il n'est pas nécessaire de classer les liquides ayant un point d'éclair supérieur à 35° C dans la catégorie 3 si l'épreuve de combustion entretenue du point L 2, partie III, section 32, du Manuel d'épreuves et de critères des Nations unies a donné des résultats négatifs. Toutefois, cette remarque n'est pas valable en cas de température ou de pression élevée, et ces liquides doivent alors être classés dans cette catégorie. Quantité seuil bas au sens de l'article R. 511-10 : 10 t. Quantité seuil haut au sens de l'article R. 511-10 : 50 t.	A	2
4330.2	La quantité totale susceptible d'être présente dans les installations y compris dans les cavités souterraines étant : 2. Supérieure ou égale à 1 t mais inférieure à 10 t (1) Conformément à la section 2.6.4.5 de l'annexe I du règlement (CE) n° 1272/2008, il n'est pas nécessaire de classer les liquides ayant un point d'éclair supérieur à 35° C dans la catégorie 3 si l'épreuve de combustion entretenue du point L 2, partie III, section 32, du Manuel d'épreuves et de critères des Nations unies a donné des résultats négatifs. Toutefois, cette remarque n'est pas valable en cas de température ou de pression élevée, et ces liquides doivent alors être classés dans cette catégorie. Quantité seuil bas au sens de l'article R. 511-10 : 10 t. Quantité seuil haut au sens de l'article R. 511-10 : 50 t.	DC	
4331.text	Liquides inflammables de catégorie 2 ou catégorie 3 à l'exclusion de la rubrique 4330. La quantité totale susceptible d'être présente dans les installations y compris dans les cavités souterraines étant :		
4331.1	1. Supérieure ou égale à 1000 t Quantité seuil bas au sens de l'article R. 511-10 : 5 000 t. Quantité seuil haut au sens de l'article R. 511-10 : 50 000 t.	A	2
4331.2	2. Supérieure ou égale à 100 t mais inférieure à 1000 t Quantité seuil bas au sens de l'article R. 511-10 : 5 000 t. Quantité seuil haut au sens de l'article R. 511-10 : 50 000 t.	E	
4331.3	3. Supérieure ou égale à 50 t mais inférieure à 100 t Quantité seuil bas au sens de l'article R. 511-10 : 5 000 t. Quantité seuil haut au sens de l'article R. 511-10 : 50 000 t.	DC	
4510.text	Dangereux pour l'environnement aquatique de catégorie aiguë 1 ou chronique 1.		

	SAFETY DATA SHEET	Page : 13 / 15
		Revision nr : 5.0
	Derbiprimer GC	Issue date : 26/10/2021
		Supersedes : 02/12/2019

4510.1	La quantité totale susceptible d'être présente dans l'installation étant : 1. Supérieure ou égale à 100 t Quantité seuil bas au sens de l'article R. 511-10 : 100 t. Quantité seuil haut au sens de l'article R. 511-10 : 200 t.	A	1
4510.2	La quantité totale susceptible d'être présente dans l'installation étant : 2. Supérieure ou égale à 20 t mais inférieure à 100 t Quantité seuil bas au sens de l'article R. 511-10 : 100 t. Quantité seuil haut au sens de l'article R. 511-10 : 200 t.	DC	

Germany

Regulatory reference	: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)
Risk classification according to VbF	: A II - Liquids with a flashpoint between 21°C and 55°C
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

Waterbezwaarlijkheid	: A (1) - zeer vergiftig voor in water levende organismen kan in aquatische milieu op lange termijn schadelijke effecten veroorzaken
Saneringsinspanningen	: A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken
SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

Denmark

Recommendations Danish Regulation	: Pregnant/breastfeeding women working with the product must not be in direct contact with the product
-----------------------------------	--

Norway

This safety datasheet has been prepared according to Norwegian legislation.	: FOR 2002-07-16 nr 1139: Forskrift om klassifisering, merking mv. av farlige kjemikalier; Forskrift om klassifisering, merking og emballering av stoffer og stoffblandinger (CLP); FOR 2008-05-30 nr 516: Forskrift om registrering, vurdering, godkjenning og begrensnig av kjemikalier (REACH-forskriften)
---	---

15.2. Chemical safety assessment


For the following substances of this mixture a chemical safety assessment has been carried out

For the following substances of this mixture a chemical safety assessment has been carried out
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2%
Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)

SECTION 16: Other information

Indication of changes:

1	SDS Version (obsolete)	Modified	
---	------------------------	----------	--

	SAFETY DATA SHEET		Page : 14 / 15
			Revision nr : 5.0
			Issue date : 26/10/2021
	Derbiprimer GC		Supersedes : 02/12/2019

1	Issue date	Added	
2.2	Hazard statements (CLP)	Modified	
2.3	ED	Added	
3.2	Composition	Modified	
11.2	Adverse health effects caused by endocrine disrupting properties	Added	
12.6	Adverse effects on the environment caused by endocrine disrupting properties	Added	
14.7	Maritime transport in bulk according to IMO instruments	Added	
15.1	Installations classées	Modified	
15.1	Saneringsinspanning en	Modified	
15.1	Saneringsinspanning en	Added	
16	Other information	Added	
16	Other information	Modified	
	Information with regard to physical hazard classes	Added	

Abbreviations and acronyms:

ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods Code
LEL = Lower Explosive Limit/Lower Explosion Limit
UEL = Upper Explosion Limit/Upper Explosive Limit
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
EC50 = Median Effective Concentration
LC50 = Median lethal concentration
LD50 = Median lethal dose
TLV = Threshold limits
TWA = time weighted average
STEL = Short term exposure limit
persistent, bioaccumulating and toxic (PBT).
vPvB = very persistent and very bioaccumulating
WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the : ECHA (European Chemicals Agency). SDS Manufacturer/Supplier. datasheet

Training advice : Training staff on good practice. Manipulations are to be done only by qualified and authorised persons.

Other information : Assessment/classification CLP. Article 9. Calculation method. Physicochemical hazard assessment: Information given is based on tests on the mixture itself.

Full text of H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3

	SAFETY DATA SHEET	Page : 15 / 15
		Revision nr : 5.0
		Issue date : 26/10/2021
	Derbiprimer GC	Supersedes : 02/12/2019

Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.